

Aviva Fungisan

8308000210

Aqueous disinfectant solution for the treatment of **fungus and algae infested surfaces**, for indoor and outdoor use, for **DIY and professional use**.

PRODUCT DESCRIPTION

General

Low-odour, water-based sanitation concentrate to support the cleaning of masonry and wood infested with fungus and algae.

The product is formulated without added heavy metals and phenols.

Intact coatings are not attacked.

Special properties

- The active substances used provide a disinfectant effect for the pre-treatment of surfaces infested with algae and fungi.

Active substances

4,8 g/kg (0,48%) Benzalkonium chloride

0,48 g/kg (0,048%) Octylisothiazolinon

- French ordinance DEVL1104875A** regarding the marking of construction coating products for their emission of volatile pollutants: A+



Application area

- Surfaces attacked by mold, algae and green covering.



PROCESSING

Instructions for use



- The temperature of the product and object, and the room temperature must be at least + 5 °C.
- The optimal conditions for use are between 15 – 25 °C with a relative atmospheric humidity between 40 – 80 %.
- Do not process it under conditions of intense sunlight, rain, extremely high humidity, strong wind or pending frost. Cover those surfaces well that are not to be treated.
- Ready for use, do not dilute!
- A treatment should not be done on a wet surface, otherwise there is no penetration effect.
- The active substances used are water-soluble and degradable, therefore a finishing coat is recommended.
- Due to its water-solubility Aviva Fungisan 8308000210 cannot be used as an additive for topcoats for external use.

06-20 (supersedes 06-19) ZKL 8308

ADLER-Werk Lackfabrik, A-6130 Schwaz

Phone: 0043/5242/6922-301, Fax: 0043/5242/6922-309, email: technical-support@adler-lacke.com

Our instructions for use are based on knowledge available currently and shall guide the buyer/user to the best of one's knowledge, but, however, must be clarified for the areas of application and processing conditions on a case-to-case basis. The buyer/user is responsible for deciding on the suitability and use of the delivered product, which is why it is recommended to produce a sample to check the suitability of the product. Our general terms and conditions of sale are otherwise applicable. All previous data sheets are rendered invalid with the issue of this one. Rights reserved for the modification of the container sizes, colour shades and degrees of gloss available.

Application technique

Application method	Brushing
Yield per application (m ² /l)	approx. 8 m ²

Preferably with a paint-brush or brush.

The shape, the properties and moisture of the substrate affect the consumption/yield. Accurate values for consumption must be obtained by applying trial coats in advance.

Drying times

(at 23 °C and 50 % rel. humidity)



Subsequent coating	after approx. 24 hours
--------------------	------------------------

The figures given above are reference values. The drying time depends on the type of substrate, coat thickness, temperature, air exchange and relative atmospheric humidity.

Cleaning the working equipment

With water immediately after use.

SUBSTRATE**Type of substrate**

Mineral substrates infested with algae, green covering or fungus, old coatings and wood.

Substrate property (or condition)

The substrate must be dry, clean, capable of holding the paint, free from separating substances such as grease, wax, silicone, resin etc. and free from wood dust, as well as tested for suitability for coating. Please observe and follow ÖNORM B 2230 Part 2.

See also VOB, Part C, DIN 18363, Paragraph 3; painting and coating work.

Preparation of the substrate

- Any coatings that cannot be recoated must be removed thoroughly.
- Cover adjacent plants and sensitive surfaces which should not be cleaned or rinse immediately with water after use.
- Adhering impurities as well as efflorescence, algae, green covering or fungi must be removed by suitable cleaning procedures.
- In the case of wet cleaning or for sewage water, the legal regulations regarding the disposal of sewage water must be observed.

COATING SYSTEM**Product application**

1 x Aviva Fungisan 8308000210

Intermediate drying: approx. 24 hours

In case of severe infestation or highly absorbent surfaces, we recommend using the product twice.

Subsequent coating


After 24 hours, the desired ADLER facade paint as well as Aviva living space paint and on wood the corresponding ADLER wood paint can be applied.

Please observe the relative technical data sheets of the products.

ORDERING INFORMATION

Size of trading unit	1 l; 5 l
Colour shades / degrees of gloss	Farblos 8308000210

FURTHER DETAILS

Durability / storage


At least 3 years in the original sealed containers.

Make sure the product is protected against moisture, direct sunlight, frost and high temperatures (above 30 °C).

Safety-related information


Further information on the subject of safety during transport, storage and handling as well as disposal can be found in the relevant safety data sheet. The current version can be accessed on the Internet at **www.adler-lacke.com**.

Recycle only those containers whose residues have been emptied out. You may dispose of liquid material residues as water-based paint and varnish waste and dried-up material residues as cured paints or as household garbage.

Use biocides safely. Always read the label and the product information before use.

It is recommended to use safety gloves and safety glasses while processing.
